

Safety Data Sheet

Diesel B07

Íslensk aðlögun 31/5/2021

Revision date: 30/11/2018
Version: 1.0.0

SECTION 1: Identification of the substance/preparation and of the company/undertaking

1.1. Product identifier

Trade name: Diesel B07

Synonyms: Auto Diesel

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Fuel.

1.3. Details of the supplier of the safety data sheet

Supplier

Company: Equinor Refining Denmark A/S
Address: Melbyvej 17
Zip code: 4400
City: Kalundborg
Country: DENMARK
E-mail: chem@equinor.com
Phone: +45 59574500

Atlantsólía
Lónsbraut 2
220
Hafnarfjörður
Ísland
atlantsolia@atlantsolia
591-3100

1.4. Emergency Telephone Number

1 1 2

Eitrunarmiðstöð Landspítalans 543 2222

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification: Flam. Liq. 3;H226 Asp. Tox. 1;H304 Skin Irrit. 2;H315 Acute Tox. 4;H332 Carc. 2;H351 STOT RE 2;H373 Aquatic Chronic 2;H411

Most serious harmful effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Harmful if inhaled. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects. The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication.

2.2. Label elements

Pictograms



Signal word: Danger

Contains

Substance: Fuels, Diesel;

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

H-phrases

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

P-phrases

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.

2.3. Other hazards

The product does not contain any PBT or vPvB substances.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No	EC No	REACH Reg. No.	Concentration	Notes	CLP-classification
Fuels, Diesel	68334-30-5	269-822-7	01-2119484664-27-0021	85 - 95%		Flam. Liq. 3;H226 Asp. Tox. 1;H304 Skin Irrit. 2;H315 Acute Tox. 4;H332 Carc. 2;H351 STOT RE 2;H373 Aquatic Chronic 2;H411
Alkanes, C10-20, branched and linear	928771-01-1	618-882-6	01-2119450077-42	0 - 10%		Asp. Tox. 1;H304
Fatty acid methyl ester	67762-38-3	267-015-4	01-2119471664-32-0085	5 - 10%		

Please see section 16 for the full text of H-phrases.

Ingredient comments: Max. 10 mg/kg sulphur.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:	Seek fresh air. Seek medical advice in case of persistent discomfort.
Ingestion:	Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. If vomiting occurs, keep head low so that stomach contents do not enter lungs. Immediately call a POISON CENTER or doctor/physician.
Skin contact:	Remove contaminated clothing. Wash skin with soap and water. Seek medical advice in case of persistent discomfort.
Eye contact:	Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.
Burns:	Flush with water until pain ceases. Remove clothing that is not stuck to the skin - seek

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.

General: When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Irritating to skin - may cause reddening. May cause chemical pneumonia if ingested or vomited. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms. No special immediate treatment required.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Extinguish with powder, foam or water mist. Use water or water mist to cool non-ignited stock.

Unsuitable extinguishing media: Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

Can generate harmful flue gases containing carbon monoxide in the event of fire.

5.3. Advice for fire-fighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air. Wear Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Stay upwind/keep distance from source. Keep unnecessary personnel away. Wear gloves. Wear suitable protective clothing. Wear safety goggles if there is a risk of eye splash. In case of insufficient ventilation, wear respiratory protective equipment. Smoking and naked flames prohibited.

For emergency responders: In addition to the above: Protective suit equivalent to EN 368, type 3, is recommended.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water. Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent, non-combustible material and transfer to suitable waste containers.

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage

Safety Data Sheet

Diesel B07

 Revision date: 30/11/2018
 Version: 1.0.0

7.1. Precautions for safe handling

Work under effective process ventilation (e.g. local exhaust ventilation). Running water and eye wash equipment must be available. A safety shower should be available. A workplace assessment must be conducted to ensure that employees are not exposed to effects that may involve a risk during pregnancy. Do not store, use and/or consume foods, beverages or tobacco products in the work room. Store personal protective equipment separately from other clothing. Wash hands before breaks, before using restroom facilities, and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Keep in tightly closed original packaging. Store in a well-ventilated area. Do not store with the following: Strong oxidisers. Do not expose to heat (e.g. sunlight).

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit: Contains no substances subject to reporting requirements Rg.

Legal basis: [390/2009, um mengunarmörk. Síðast breytt í nóvember 2020](#)

PNEC

Fuels, Diesel, cas-no 68334-30-5				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (freshwater)	0,083 mg/l	1	Statistic extrapolation	

DNEL - workers

Fuels, Diesel, cas-no 68334-30-5					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	2,9 mg/m ³ /8h	24	NOEL		
Inhalation DNEL (long-term exposure - systemic effects)	68 mg/m ³ /8h	7,5	NOEL		
Dermal DNEL (acute/short-term exposure - systemic effects)	4300 mg/m ³ /15m	7,5	NOAEC		

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	42 mg/kg bw/day				
Inhalation DNEL (long-term exposure - systemic effects)	147 mg/m ³				

DNEL - general population

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018

Version: 1.0.0

Fuels, Diesel, cas-no 68334-30-5					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (acute/short-term exposure - systemic effects)	2600 mg/m ³ /15m	7,5	NOAEC		
Dermal DNEL (long-term exposure - systemic effects)	1,3 mg/kg	24	NOAEL		
Inhalation DNEL (long-term exposure - systemic effects)	20 mg/m ³ /24h	7,5	NOEL		
Alkanes, C10-20, branched and linear, cas-no 928771-01-1					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - systemic effects)	18 mg/kg bw/day				
Inhalation DNEL (long-term exposure - systemic effects)	94 mg/m ³				

8.2. Exposure controls

Exposure controls:	See enclosed exposure scenarios for further information.
Appropriate engineering controls:	Wear the personal protective equipment specified below.
Personal protective equipment, eye/face protection:	Wear safety goggles if there is a risk of eye splash. Eye protection must conform to EN 166.
Personal protective equipment, skin protection:	Wear suitable protective clothing.
Personal protective equipment, hand protection:	Light use (small volume, shortterm contact (below 10 min.)): Wear gloves. Type of material: Nitrile rubber. Medium use (medium volume, medium contact (1-2 hours)): Wear gloves. Type of material: Nitrile rubber. Heavy use (high volume, longterm contact (more than 2 hours)): Wear gloves. Type of material: Nitrile rubber. Penetration time: >8 hours. Gloves must conform to EN 374.
Personal protective equipment, respiratory protection:	Light use (small volume, shortterm contact (below 10 min.)): Not required. Medium use (medium volume, medium contact (1-2 hours)): In case of insufficient ventilation, wear respiratory protective equipment. Filter type: A. Heavy use (high volume, longterm contact (more than 2 hours)): In case of insufficient ventilation, wear respiratory protective equipment. Filter type: A. Respiratory protection must conform to one of the following standards: EN 136/140/145.
Environmental exposure controls:	Ensure compliance with local regulations for emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter	Value/unit
-----------	------------

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

State	Liquid
Colour	Brown
Odour	Diesel.
Solubility	No data
Explosive properties	No data
Oxidising properties	No data

Parameter	Value/unit	Remarks
pH (solution for use)	No data	
pH (concentrate)	No data	
Melting point	-40 - 6 °C	
Freezing point	No data	
Initial boiling point and boiling range	141 - 500 °C	
Flash Point	56 °C	
Evaporation rate	No data	
Flammability (solid, gas)	No data	
Flammability limits	> 225 °C	
Explosion limits	No data	
Vapour pressure	0.40 kPa	(40 °C)
Vapour density	No data	
Relative density	0.80 - 0.91	
Partition coefficient n-octanol/water	No data	
Auto-ignition temperature	> 225 °C	
Decomposition temperature	No data	
Viscosity	> 1.30 mm ² /s	(40 °C)
Odour threshold	No data	

9.2 Other information

Parameter	Value/unit	Remarks
Pour point:	-40 - 6 °C	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with the following: Strong oxidisers.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid heating and contact with ignition sources.

10.5. Incompatible materials

Strong oxidisers.

10.6. Hazardous decomposition products

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 7600mg/kg		OECD 420	

Fatty acid methyl ester, cas-no 67762-38-3

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 5000mg/kg			

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 2000mg/kg		Method EC B1 tris	

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met. Ingestion may cause discomfort.

Acute toxicity - dermal

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		4300 mg/kg bw/day		OECD 434	

Fatty acid methyl ester, cas-no 67762-38-3

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		2000 mg/kg			

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 2000mg/kg		Method EC B3	

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Acute toxicity - inhalation

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50 (gases)	4h	4.1 mg/l		OECD 403	

Harmful by inhalation.

Skin corrosion/irritation

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit		24h		Irritating	OECD 404	

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
				Non-irritating	Method EC B4 og B5	

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

Irritating to skin - may cause reddening.

Serious eye damage/eye irritation

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit		24h		Non-irritating	OECD 405	

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met. Temporary irritation.

Respiratory sensitisation or skin sensitisation

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Guinea pig				Non-sensitising	OECD 406	

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
				Non-sensitising	Method EC B6	

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Germ cell mutagenicity

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
				No mutagenic effects observed.	Method EC B4 og B5	

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Carcinogenic properties

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Mouse		3 weeks		Neoplastic effects observed.	OECD 451	

Suspected of causing cancer.

Reproductive toxicity

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	NOAEC Inhalation		> 401ppm			
	NOAEL (Dermal)	20d	125 mg/kg/day			

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
				No indication of impairment of fertility or teratogenic damage.	OECD 416	

The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met.

Single STOT exposure:

The product releases organic solvent vapours which may cause lethargy and dizziness. At high concentrations, the vapours may cause headache and intoxication. The product does

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

not have to be classified. Test data are not available.

Repeated STOT exposure

Fuels, Diesel, cas-no 68334-30-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	NOAEL (Dermal)	28d	0.5 ml/kg			
Rat	NOAEL (Dermal)	90d	30 mg/kg/day			
Rat	Inhalation NOAEC	90d	> 1710mg/m3			

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
				No known effects.	OECD 408	

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: May cause chemical pneumonia if ingested or vomited.

Other toxicological effects: None known.

SECTION 12: Ecological information

12.1. Toxicity

Fuels, Diesel, cas-no 68334-30-5

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Fish	Oncorhynchus mykiss	14d	14dNOEL	0.083 mg/l			
Crustacea	Daphnia magna	21d	21dNOEL	0.21 mg/l			
Fish	Oncorhynchus mykiss	96h	96hLC50	21 mg/l			
Crustacea	Daphnia magna	48h	48hEC50	68 mg/l			
Algae	Name of species not specified	72h	72hIC50	22 mg/l			

Fatty acid methyl ester, cas-no 67762-38-3

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Algae	Name of species not specified	72h	72hErC50	> 0.131mg/l		OECD 201	
Crustacea	Daphnia sp.	48h	48hEC50	2504 mg/l		OECD 202	

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
LOEC	Sediment organisms	10d		1165 mg/kg			
NOEC	Sediment organisms	10d		373 mg/kg			
Fish	Name of species not specified	96h	96hLC50	> 1000mg/l		WAF (OECD 203)	

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

Crustacea	Name of species not specified	48h	48hEC50	> 100mg/l		OECD 202	
LOEC	Daphnia	21d		32 mg/l		OECD 211	
NOEC	Daphnia	21d		> 1mg/l		OECD 211	
Algae	Name of species not specified	72h	72hEC50	> 100mg/l		OECD 201	

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Fatty acid methyl ester, cas-no 67762-38-3

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
					Readily biodegradable.		

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
					Readily biodegradable.	OECD 301 B	

The product contains at least one readily biodegradable substance.

12.3. Bioaccumulative potential

Alkanes, C10-20, branched and linear, cas-no 928771-01-1

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
			Log Kow	> 6.5			

Bioaccumulation can be expected.

12.4. Mobility in soil

Not expected to be mobile in soil. Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Empty, cleansed packaging should be disposed of for recycling. Collect spills and waste in closed, leak-proof containers for disposal at the local hazardous waste site. Uncleansed packaging is to be disposed of via the local waste-removal scheme.

Category of waste:

EWC code: Depends on line of business and use, for instance 13 07 01* fuel oil and diesel

Absorbent/cloth contaminated with the product: EWC code: 15 02 02 absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances.

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN-No.: 14.2. UN proper shipping name:	1202 DIESEL FUEL	14.4. Packing group: 14.5. Environmental hazards:	III The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.
14.3. Transport hazard class(es): Hazard label(s): Hazard identification number: Other Information:	3 3 30 -	Tunnel restriction code:	D/E

Inland water ways transport (ADN)

14.1. UN-No.: 14.2. UN proper shipping name:	1202 DIESEL FUEL	14.4. Packing group: 14.5. Environmental hazards:	III The product must be labelled as an environmental hazard (symbol: fish and tree) in packaging sizes of more than 5 kg/l.
14.3. Transport hazard class(es): Hazard label(s): Transport in tank vessels:	3 3 F + CMR + N2	Other Information:	-

Sea transport (IMDG)

14.1. UN-No.: 14.2. UN proper shipping name:	1202 DIESEL FUEL	14.4. Packing group: 14.5. Environmental hazards:	III The product must be labelled as a Marine Pollutant (MP) in packaging sizes of more than 5 kg/l.
14.3. Transport hazard class(es): Hazard label(s): EmS: Other Information:	3 3 F-E, S-E -	Environmental Hazardous Substance Name(s): IMDG Code segregation group:	Fuels, Diesel - None -

Air transport (ICAO-TI / IATA-DGR)

14.1. UN-No.: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): Hazard label(s):	1202 DIESEL FUEL 3 3	14.4. Packing group: 14.5. Environmental hazards: Other Information:	III - -
--	-------------------------------	---	---------------

14.6. Special precautions for user

None.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Provisions: Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product.
Directive 2012/18/EU (Seveso), E2 Hazardous to the Aquatic Environment in Category Chronic 2 : Column 2: 200 t, Column 3: 500 t.
Directive 2012/18/EU (Seveso), P5c FLAMMABLE LIQUIDS: Column 2: 5000 t, Column 3: 50000 t.
Directive 2012/18/EU (Seveso), Petroleum products and alternative fuels (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams) (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)): Column 2: 2500 t, Column 3: 25000 t.

Covered by:

Council Directive 92/85/EEC of 19 October 1992 on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding
Statutory Instrument 2002 No. 2677. The Control of Substances Hazardous to Health Regulations 2002.

15.2. Chemical Safety Assessment

REACH Reg. No.	Substance name
01-2119450077-42	Alkanes, C10-20, branched and linear
01-2119471664-32-0085	Fatty acid methyl ester
01-2119484664-27-0021	Fuels, Diesel

SECTION 16: Other information

Version history and indication of changes

Version	Revision date	Responsible	Changes
1.0.0	30/11/2018	CGJ/Bureau Veritas HSE Denmark AS	New SDS

Abbreviations: PBT: Persistent, Bioaccumulative and Toxic
vPvB: Very Persistent and Very Bioaccumulative
STOT: Specific Target Organ Toxicity
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration

Other Information: This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.
Exposure scenarios are enclosed as appendices.

Training advice: A thorough knowledge of this safety data sheet should be a prerequisite condition.

Classification method: Calculation based on the hazards of the known components. Test data.

Safety Data Sheet

Diesel B07

Revision date: 30/11/2018
Version: 1.0.0

List of relevant H-statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

SDS is prepared by

Company:	Bureau Veritas HSE Denmark A/S
Address:	Oldenborggade 25
Zip code:	7000
City:	Fredericia
Country:	DENMARK
E-mail:	infohse@dk.bureauveritas.com
Phone:	+45 75 50 88 11
Fax:	+45 75 50 88 10
Homepage:	www.hse.bureauveritas.dk

Íslensk Aðlögun
Mannvit
Urðarhvarf 6
203
Kópavogur Ísland
mannvit@mannvit.is
422 3000
www.mannvit.is

Document language: GB